

RECEIVED
CENTRAL FAX CENTERApplication Serial No. 10/784,974
Reply to Office Action dated August 10, 2005

NOV 07 2005

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A cooking appliance comprising:
 - a cooktop;
 - a plurality of heating zones arranged on the cooktop, at least one of said plurality of heating zones including a first heating element and a second heating element; and
 - a control element operatively connected to each of the first and second heating elements and movable from a home position through a temperature adjustment zone, wherein initial movement of the control element from the home position in a first direction activates only the first heating element at an initial temperature, with continued movement in the first direction increasing an operating temperature of the first heating element and, initial movement of the control element from the home position in a second direction activates both the first and second heating elements at an initial temperature, with continued movement in the second direction increasing a combined operating temperature of the first and second heating elements such that said control element being is movable through the temperature adjustment zone to regulate operation of the first heating element or both the first and second heating elements respectively,
2. (original) The cooking appliance according to claim 1, wherein movement of the control element through the temperature adjustment zone back to the home position deactivates the at least one of the plurality of the heating zones.
3. (original) The cooking appliance according to claim 1, further comprising:
 - a controller operatively connected to the control element; and
 - first and second relays operatively connected to the first and second heating elements respectively, wherein the controller activates the first relay when the control

Application Serial No. 10/784,974
Reply to Office Action dated August 10, 2005

element is moved in the first direction and both the first and second relays when the control element is moved in the second direction.

4. (original) The cooking appliance according to claim 3, wherein the control element includes a variable resistor, said controller being adapted to detect whether the control element is moved in the first or second direction based upon a change in resistance of the variable resistor.

5. (original) The cooking appliance according to claim 1, wherein the second heating element is arranged about the first heating element.

6. (original) The cooking appliance according to claim 1, further comprising: a display for indicating operation of at least one of the first heating element or both the first and second heating elements.

7. (original) The cooking appliance according to claim 1, wherein the control element is rotatable through the temperature adjustment zone.

8. (original) The cooking appliance according to claim 7, wherein the control element is rotatable through nearly 360° in the temperature adjustment zone to regulate operation of either the first heating element or both the first and second heating elements.

9. (currently amended) A cooking appliance comprising:

a cooktop;

a plurality of heating zones arranged on the cooktop, at least one of said plurality of heating zones including a first heating element and a second heating element; and

control means operatively connected to each of the first and second heating elements and movable from a home position through a temperature adjustment zone, wherein initial movement of the control means from the home position in a first direction activates only the first heating element at an initial temperature, with continued

Application Serial No. 10/784,974
Reply to Office Action dated August 10, 2005

movement in the first direction increasing an operating temperature of the first heating element and initial movement of the control means from the home position in a second direction activates both the first and second heating elements at an initial temperature, with continued movement in the second direction increasing a combined operating temperature of the first and second heating elements such that said control means being is movable through the entire temperature adjustment zone to regulate operation of the first heating element or both the first and second heating elements respectively.

10. (original) The cooking appliance according to claim 9, wherein the control means is movable through the temperature adjustment zone back to the home position to deactivate the at least one of the plurality of heating zones.

11. (original) The cooking appliance according to claim 9, further comprising:
a controller operatively connected to the control means; and
first and second relay means operatively connected to the first and second heating elements respectively, wherein the controller activates the first relay means when the control means is moved in the first direction and both the first and second relays when the control element is moved in the second direction.

12. (original) The cooking appliance according to claim 11, wherein the control means includes a variable resistor, said controller being adapted to detect whether the control means is moved in the first or second direction based upon a change in resistance of the variable resistor.

13. (original) The cooking appliance according to claim 9, wherein the second heating element is arranged about the first heating element.

14. (original) The cooking appliance according to claim 9, further comprising: a display for indicating operation of at least one of the first heating element or both the first and second heating elements.

Application Serial No. 10/784,974
Reply to Office Action dated August 10, 2005

15. (original) The cooking appliance according to claim 9, wherein the control means is rotatable through the temperature adjustment zone.

16. (original) The cooking appliance according to claim 15, wherein the control element is rotatable through nearly 360° in the temperature adjustment zone to regulate operation of either the first heating element or both the first and second heating elements.

17. (currently amended) A method of operating a heating zone having first and second heating elements on a cooktop of a cooking appliance comprising:

shifting a control element from a home position into a temperature adjustment zone;

sensing a direction of movement of the control element from the home position;

activating only the first heating element if the control element is shifted in a first direction and activating both the first and second heating elements if the control element is shifted in a second direction; and

enabling temperature control for either the first heating element or both of the first and second heating elements, depending upon the direction of movement of the control element, throughout the entire temperature adjustment zone until the control element is repositioned in the home position with initial movement of the control element in the first direction activating the first heating element at an initial temperature, with continued movement in the first direction increasing an operating temperature of the first heating element and initial movement of the control element in the second direction activating both the first and second heating elements at an initial temperature, with continued movement in the second direction increasing a combined operating temperature of the first and second heating elements.

18. (original) The method of claim 17, wherein sensing the direction of movement of the control element includes detecting changes in resistance of a variable resistor operatively connected to the control element.

Application Serial No. 10/784,974
Reply to Office Action dated August 10, 2005

19. (original) The method of claim 18, further comprising:

activating a first relay to operate the first heating element if the control element is shifted in the first direction; and

activation both the first relay and a second relay to operate both of the first and second heating elements if the control element is shifted in the second direction.

20. (original) The method of claim 17, further comprising: displaying an operational state of at least one of the first and second heating elements.